

Roof Ladder

1 Product type's unique identification code **CWLRL01**

2 Intended use:

- Access route for pitched roofs on buildings.
- Attachment of personal fall protection equipment.
- Corrosivity class C4 40 years

3 Manufacturer:

CW Lundberg Industri AB - Landsvägen 52 - Box 138 - SE-792 22 Mora, Sweden
Tel. +46 250 55 35 00 - info@cwlundberg.com

4 System for assessment of the construction product's performance **System 3**

5a Harmonised standard: **EN 12951:2004**

5b Reported body:

RISE, Research Institutes of Sweden, no. 0402 has performed the type testing.

6 Specified performance:

<i>Essential properties</i>	<i>Performance</i>	<i>Harmonised standard</i>
Mechanical strength	Fulfils ¹	EN 12591:2004
- Static load	Fulfils	
- Torque resistant	Fulfils ¹	
- Dynamic energy absorption capacity	Fulfils ¹	
Characteristics upon external fire impact and reaction in case of fire	A1	
Durability	Fulfils ¹	

Note 1: Roof ladder is type A upon the addition of roof steps according to the applicable installation instruction

7 Product performance specified in Section 1 is consistent with the product performance specified in Section 6. This Declaration of Performance is issued under the responsibility for the manufacturer, as stated under Section 3, pursuant to the type testing performed by the reported organ as stated in Section 5h.

Signed on behalf of the manufacturer by:



Thomas Lundberg
Managing Director

Mora, 1 Feb 2019

